

HOPPER TOPPER POWERLIFT



Example picture; machine equipped with accessories





The Hopper Topper Powerlift transfer pump will help keep your production flowing smooth. With our gentle pumping technology, your product will be quickly transferred without sacrificing quality. No matter if you process smooth cremes or doughs, chunky fruit- or nut fillings, soups, salads or sauces, the Unifiller transfer pump perfectly transports all kinds of products without affecting its properties.

ADVANTAGES:

- Non-stop production and no heavy lifting required
- Pump designed to simulate gentle hand scooping
- Ability to draw product directly from the bowl
- Ergonomic power lift allows to change bowls without lifting
- Optical product sensor allows to maintain product level in hopper resulting in continuous production and improved portion control
- Tool free disassembly for quick and easy cleaning
- Versatility fits most mixing bowls

FEATURES:

- Mobile all stainless steel construction stand with adjustable height to fit into different bowl sizes
- Flow control to adjust pump speed for different products
- Ergonomic power lift technology
- Standard and extended depth versions available






HOPPER TOPPER POWERLIFT




SYSTEM INCLUDES

• Quick start guide and spare parts kit

SPECIFICATIONS	DRAWING	POWERLIFT	POWERLIFT EXTENDED
Height			
Power lift distance	А	71 cm	91 cm
Max. ceiling height in up position	В	290 cm	328 cm
Max. bowl rim clearance in up position	С	109 cm	115 cm
Max. bowl bottom to floor clearance	D	38 cm	28 cm
Distance bowl inlet and outlet (max. bowl depth)	E	62 cm	87 cm
Frame			
Inside width	F	63 cm	82 cm
Bottom frame height	G	15 cm	17 cm
Pipe work reach	Н	193 cm	193 cm
Max. ceiling height in low position	J	208 cm	226 cm







SHIPPING INFORMATION

- Dimensions: Powerlift: 135 cm x 97 cm x 56 cm;
- Weight: Powerlift: 95 kg;

VOLUME

• 11 - 49 litres/min.



SPEED

Adjustable with speed control



POWER

- Air: 4 CFM at 80 psi (113 litres/min. at 5.5 bar)
- Electric: 230 V, 1 amp



PARTICLE SIZE

• Up to 25 mm soft particulates

CERTIFICATES







Unifiller Europe GmbH Hofmattstr. 16 79541 Lörrach Germany Tel +49 7621 583 6310 Fax +49 7621 583 6318 www.unifiller-europe.com