

UNIVERSAL 2000i SERVO FS

The Universal 2000i Servo FS is a unique, servo electronically controlled piston depositor for the Food Processing Industries. This heavy duty depositor is designed for ultimate sanitation requirements in Food Service areas and is perfectly suitable for the quick and clean depositing of large volumes and products with extra big chunks. Ensure the gentle processing of relatively viscous to liquid products with and without chunks such as batters, fillings, sauces, soups, pie fillings and many more - without affecting the product textures.



ADVANTAGES:

- 27% more powerful than the pneumatic version
- Speed and portion accuracy
- Stainless steel construction - all food contact parts are dishwasher safe
- Ergonomic Powerlift technology for easy and convenient filling of the hopper
- Handles chunky to aerated products, ability to deposit extra large chunks
- Programmable volume and speed - reduces the time spent to set up and change over
- Programmable pre-charge, suck back and reload speed for optimum control over densities
- Standalone machine or integrated into a production systems operating in slave mode
- Allows automated depositing systems to automatically adjust multiple depositors in one step
- Connect to inline check weigh system for automatic volume adjustments
- Large deposit range: 25 ml - 2750 ml
- Large 79 litres conical hopper

FEATURES:

- PLC control system with color touch screen enclosed within a wash down control panel
- 6 programmable modes for depositing, spreading, liquid deposits and multi shots
- Electronic recipe storage for 100 recipes
- Heavy duty all stainless steel construction
- Sloped horizontal cover surfaces for improved food safety and sanitation
- Pneumatic control system designed to work in hot and cold environments



UNIVERSAL 2000i SERVO FS




FEATURE	STANDARD PISTON DEPOSITOR	SERVO DEPOSITOR
		27% more powerful than pneumatic depositors
Deposit Speed and Volume	Manual Adjustment	😊 Automatic
Minimum Deposit Size	15% of maximum deposit	😊 5% of maximum deposit
Cycle Counter	✗	😊
Pre-Charge and Suckback	✗	😊 Yes, electronically adjustable
Electronic Recipe Storage	✗	😊 100 recipe storage capacity
Liquid deposit mode	✗ No, liquids may splash	😊 Slow start and finish to eliminate splashing
Spreading Applications	Okay	😊 Excellent for spreading accurate portions
Check Weight compatibility	✗	😊 Check weigher can automatically adjust
Plant Network compatible	✗	😊 Statistical data collect and reports

SYSTEM INCLUDES

- Large 79 litres hopper
- Quick start guide and spare parts kit

PRODUCT CYLINDER DEPOSIT VOLUME SIZE

	MIN	MAX
5"	205 ml	2750 ml
4"	205 ml	1860 ml
2.5"	120 ml	710 ml
1.5"	25 ml	245 ml



SHIPPING INFORMATION

- Dimensions: 157 cm x 84 cm x 148 cm
- Weight: 180 kg



SPEED

- Up to 120 deposits/min. based on 20% deposit and product consistency



POWER

- Air: 3 CFM at 80 psi (170 litres/min. at 5.5 bar);
- Electric: 220V AC, Single Phase, 10 A, 50-60 Hz



PARTICLE SIZE

- Up to 38 mm cubic soft particulates

CERTIFICATES

